




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E02F 9/22	A1	(11) International Publication Number: WO 98/17873 (43) International Publication Date: 30 April 1998 (30.04.98)
(21) International Application Number: PCT/SE96/01346 (22) International Filing Date: 21 October 1996 (21.10.96) (71) Applicant (for all designated States except US): AB ÄLÖ-MASKINER [SE/SE]; Brännland 300, S-901 37 Umeå (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): LINDBERG, Arne [SE/SE]; Tjälamark 247, S-905 91 Umeå (SE). (74) Agents: ONN, Thorsten et al.; AB Stockholms Patentbyrå, Zacco & Bruhn, P.O. Box 23101, S-104 35 Stockholm (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>

(54) Title: VIBRATION DAMPENING APPARATUS FOR MOBILE MACHINES

(57) Abstract

This invention relates to an apparatus for mobile machines, preferably tractors provided with a loading unit, which is vertically adjustable by means of at least one hydraulically operable lifting cylinder, which comprises a piston means and is an integral part of a hydraulic system in the machine, the apparatus being intended to damp the vibrations which may arise in the loading unit when the machine travels on fields and bumpy roads or when using the machine in work. According to the invention the apparatus is characterized in that it comprises the combination of the following features: the mentioned lifting cylinder (1, 2) is double-acting i.e. it can activate the hydraulic medium both on its piston side and the side of the piston rod; the lifting cylinder (1, 2) on its plus side, i.e. the piston side, is connected with at least a first accumulator (8, 9) and on its minus side, i.e. the side of the piston rod, connected with another accumulator (15).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

VIBRATION DAMPENING APPARATUS FOR MOBILE MACHINES

This invention relates to an apparatus for mobile machines, preferably tractors provided with a loading unit, which is vertically adjustable by means of at least one hydraulically operable lifting cylinder, which comprises a piston means and is an integral part of a hydraulic system in the machine, the apparatus being intended to damp the vibrations which may arise in the loading unit when the machine travels on fields and on a bumpy road or when using the machine at work.

Tractors provided with loading units are common in the market. These machines as a rule have a loading unit provided with two hydraulic cylinders and comprising for instance of forks or a bucket by means of which it is possible to load or unload goods and to move goods between two points. In the later case this transport of goods may involve transportation a long distance along a bumpy road. Therewith there arise strong swingings in the machine if this one should drive into a pit. These swingings become stronger if the loading unit carries a load of any kind. Since the lifting cylinders of the loading unit during transportation on a road are locked in the certain position, there arise heavy loads on the loading unit when the machine drives into a pit, which loads are directly transmitted to the chassis of the loading machine and therefrom to the wheels of the loading machine. The result will be a very bad driving comfort for the driver of the loading machine and strains on the loading machine and its loading unit. Thus, when the driver of the machine happens to drive into a pit with the result that the machine comes into swingings, he must immediately reduce the velocity strongly in order that the swinging shall be reduced.

There are today technical solutions in the market, which shall prevent the loading machine from coming into too strong swingings when driving down into a pit. These technical solutions, however, are very complicated, which has had the consequence that the use of these ones has been limited.

The purpose of this invention is to provide a new solution of the above-mentioned problem, which is less complicated than known solutions and accordingly considerably less expensive. Furthermore, the apparatus according to the invention, due to its technical design, should be more effective than known constructions in the market.

The solution of the mentioned problem is composed of an apparatus of the kind mentioned by way of introduction, which is characterized in that it comprises the combination of the following features:

- The mentioned lifting cylinder is double-acting, i.e. it can activate the hydraulic medium both on its piston side and the side of the piston rod;

- The lifting cylinder on its plus side, i.e. the piston side, is connected with at least a first accumulator and on its minus side, i.e. the side of the piston rod, is connected with another accumulator.

Due to that fact the troubles of swinging movements of the machine are eliminated, generally speaking, whereby the riding comfort for the driver increases and the strains on the machine and the lifting unit decreases. Moreover, the safety increases considerably during the travel of the machine. The remaining features of the invention will appear more closely below.

A preferred embodiment of the invention shall be described more closely below with reference to the accompanying drawings, in which **fig. 1** is a connection diagram for a hydraulic system of which the new apparatus is an integral part, and **fig. 2** shows the application of the new apparatus on a portion of a loading machine.

Referring to **fig. 1** is shown there schematically the new invention, which according to this embodiment has two parallel-connected, hydraulically operable lifting cylinders 1, 2, which number of cylinders is very common when using vertically adjustable loading units on loading machines. Of course, it would be possible to have only one lifting cylinder.

The plus side and the minus side, respectively, of the two lifting cylinders 1, 2, i.e. the piston side and the piston rod side, respectively, of the lifting cylinders, are via a common conduit 3, 4 connected with a control valve 5, which is partly connected with a hydraulic oil pump 6, partly with a hydraulic oil tank 7. The mentioned control valve can in a known way be regulated by means of a hand lever in the driver's cab of the loading machine when raising and lowering the loading unit and is held in an inactive neutral position, when the loading machine is travelling on the road.

According to the invention the plus sides of the two lifting cylinders 1, 2 are connected with two accumulators 8, 9 via a central conduit 10, which is divided into two conduits 11, 12, each of which going to one accumulator. In each part conduit 11, 12 is a throttling means 13, 14 arranged, the purpose of which is to brake the flow to respective accumulator and by that to damp the movement of the loading unit.

Of course it would be possible to have only one accumulator on the plus side of the lifting cylinders, and therefore also such an embodiment lies within the scope of this invention.

According to the invention is further the minus side of each lifting cylinder 1,2, i.e. the cylinder portion on the piston rod side, connected with an accumulator 15, via a common conduit 16. Also the conduit 16 is provided with a throttling means 17 which is positioned prior to the accumulator 15 and has the same function as the throttling means 13, 14, i.e. to brake the flow in to the accumulator.

In fig. 2 is shown an embodiment of the apparatus according to the invention fastened on a portion of the loading machine. In this connection the same reference notations will be used for the same details in fig. 2 as in fig. 1.

The plus side of the double-acting lifting cylinder 1 is articulately fastened on the lifting arm 18 of the loading machine, the lower end of the lifting arm being articulately fastened in an attachment 19 of the machine. The piston rod 20 of the lifting cylinder 1 is with its lower end articulately fastened in the attachment 19 on a lower level, compared with the lifting arm. In the drawing is further the hydraulic oil conduit 10 marked from the plus side of the lifting cylinder to the two accumulators 8, 9 and the hydraulic oil conduit 16 to the third accumulator 15. Furthermore, in fig. 2 are also the hydraulic oil conduits 3, 4 indicated which go to the not shown control valve.

The apparatus functions in the following way:

If the loading machine provided with the loading unit drives down into a pit, the loading unit will be pressed downwards, which has the consequence that the piston of the lifting cylinder 1 is forced further into the cylinder and the hydraulic oil positioned in front of the piston on the plus side of the lifting cylinder will via the conduit 10 be pressed into the two accumulators 8, 9 via the throttling means 13, 14. Due to this arrangement the movement of the loading unit will be strongly braked up. If the piston cylinder would have been locked during the driving, which has been the normal case previously, the downwards-directed force of the loading unit would with a full force have been transmitted to the chassis of the loading machine with the troublesome consequences and risks this normally would have led to.

The flow of hydraulic oil into the two accumulators 8, 9 leads to a strong pressure increase in the same resulting in that the pressure at a certain level will press back the

hydraulic oil to the plus side of the lifting cylinder, the piston being pressed back inside the cylinder. This leads to a upwards-directed movement of the loading unit, but this movement must not be done too quickly. This difficult problem to limit the strength of upwards-directed movement is solved by means of the accumulator 15 on the minus side of the lifting
5 cylinder 1.

The fact is that when the piston moves backwards in the lifting cylinder, the hydraulic oil on the back side of the piston will be pressed out from the minus side of the lifting cylinder and into the conduit 16 to the accumulator 15, the throttling means 17
10 throttling the inflow of hydraulic oil to the accumulator, which contributes to a damping of the movement of the lifting unit. When the hydraulic oil flows into the accumulator 15, the pressure in the same will be increased. When this pressure has reached a certain level, the hydraulic oil will be pressed back into the lifting cylinder on its minus side, the vibrations of the loading unit being strongly reduced so that the lifting cylinder takes the neutral position, i.e. the loading unit takes the position it had before the loading machine drove
15 down into the pit.

The accumulator 15, connected with the minus side of the lifting cylinder, has also the favourable effect that when scraping the ground backwards by a machine provided with a loading bucket the pressure of the loading bucket, towards the ground will be very even, which leads to a better result of the work.

20 The separate throttling means 13, 14, 17 being integral parts of the apparatus could be eliminated if the conduits going to respective accumulator 8, 9, 15 are dimensioned in that way that they function as throttling means.

The new invention has a positive effect not only when driving on a bumpy road, but it leads also to a softer and more comfortable driving for all types of loading works with
25 the machine.

In the description has been spoken about tractor-borne loading unit and loading machine. Of course, the invention could be used for other types of units and machines in which a damping of sudden unit movements is of great value.

The invention is not limited to the shown and described embodiment but can be
30 modified within the scope of the following claims.

Claims

1. An apparatus for mobile machines, preferably tractors provided with a loading unit, which is vertically adjustable by means of at least one hydraulically operable lifting cylinder, which comprises a piston means and is an integral part of a hydraulic system in the machine, the apparatus being intended to damp the vibrations which may arise in the loading unit when the machine travels on fields and bumpy roads or when using the machine in work, characterized by the combination of the following features:

- The mentioned lifting cylinder (1, 2) is double-acting i.e. it can activate the hydraulic medium both on its piston side and the side of the piston rod;

- The lifting cylinder (1, 2) on its plus side, i.e. the piston side, is connected with at least a first accumulator (8, 9) and on its minus side, i.e. the side of the piston rod connected with another accumulator (15).

2. An apparatus according to claim 1, the plus side and the minus side of the lifting cylinder (1, 2) being connected with respective accumulator (8, 9, 15) via a hydraulic oil conduit (10, 16), characterized in that a separate throttling means (13, 14, 17) is arranged in respective hydraulic oil conduit.

3. An apparatus according to claim 2, the plus side of the lifting cylinder being connected with two accumulators (8, 9) via a central conduit (10), characterized in that the conduit (10) is divided into two conduits (11, 12), and that a throttling means (13, 14) is arranged in respective part conduit (11, 12).

1/2




FIG.1




FIG.2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/01346

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: E02F 9/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5147172 A (HOSSEINI), 15 Sept 1992 (15.09.92) -- -----	1-3

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 May 1997

Date of mailing of the international search report

11-06-1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Cecilia Bergold
Telephone No. +46 8 782 25 00

Information on patent family members

International application No.

PCT/SE 96/01346

Patent document
cited in search report

Publication
date

Patent family member(s)

Publication date

US 5147172 A

15/09/92

JP 5209422 A

20/08/93